

**METHOD FOR SELECTING AN APPLICATION SERVER, A RELATED CALL  
SESSION CONTROL NETWORK ELEMENT, A RELATED PRIMARY APPLICATION  
SERVER AND A RELATED CALLED USER TERMINAL**

5           The present invention relates to a Method for selecting an  
Application Server as described in the preamble of claim 1, to a related  
Call Session Control Function network element as described in the  
preamble of claim 3, a Primary Application Server as described in the  
preamble of claim 5 and to a called user terminal as described in the  
10       preamble of the respective claim 9.

          Such a method and related devices are already known in the  
art, e.g. from "*3<sup>rd</sup> Generation Partnership Project; Technical Specification  
Group Core Network; IP Multimedia (IM) Session Handling; IP Multimedia  
(IM) call model; Stage 2 (Release 5) with reference 3GPP TS 23.218 V5.2.0  
15       (2002-09)*". This document is published by the 3<sup>rd</sup> Generation Partnership  
Project (3GPP) in September 2002.

          Especially Annex C of this document, discloses an example for  
activating Application Servers using filter criteria for triggering an  
Application Server, i.e. the way Application Servers are selected and  
20       respectively invoked by the Call Session Control Function based on the  
content of filter criteria.

          An incoming call to a particular user is intercepted by the  
call control network element, called the Call Session Control  
Function, which is in charge of serving the called user. The Call  
25       Session Control Function Network Element has been pre-configured  
with this user's triggering data. When trigger conditions, called filter  
criteria, are met a certain Application Server is to be contacted and

will receive the control of this incoming call. Several Application Servers can be contacted in sequence in a certain call.

The triggering conditions describe a list of filter criteria each being linked to an application server for executing a  
5 corresponding Application service. For a number of specific cases to be described in the filter criteria a specific application is automatically pre-selected based on the triggering data for taking the control of the incoming call.

In this model of selecting Application Servers, there is no  
10 means to provide the called user with the possibility to select the Application Servers for handling the incoming call himself as the sequence of activation of call servers dealing with specific application services is predefined in the triggering conditions.

An object of the present invention is to provide a called user  
15 with a method for selecting application servers of the above known type but wherein the called user is enabled to answer an incoming call using service applications selectable by the called user. According to the invention, this object is achieved by the method as claimed in claim 1, the related\_Call\_Session Control Function network element as claimed in  
20 claim 3 together with the Primary Application Server as claimed in claim 5 and the called user terminal as claimed in claim 9.

Indeed due to the fact that a dedicated primary application server is activated upon interception of an incoming call and that this primary application server upon analysis of an incoming IP multimedia  
25 call is able to present this incoming IP multimedia call to the called party together with a set of service applications for answering the incoming IP multimedia call, where the set of service applications is determined in the analysis of the incoming call, and the called party may subsequently

select at least one service application from the presented set of service applications, the call session control network element (CSCF) based on this at least one selected service application is able to handle the incoming call by invoking at least one Application Server (AS1..Asn)  
5 corresponding to this at least one selected service application.

An additional characteristic feature of the present invention relates to the method as described in claim 2 and the call session control network element as described in claim 4.

The call session control network element further is able to  
10 invoke the at least one secondary Application Server that corresponds to the at least one selected service application.

In this way the call is amongst others handled by the at least one selected service application.

A further characteristic feature of the present invention is  
15 described in claim 6.

The call presentation information forwarding means of the primary application server is adapted to forward said call presentation information of said incoming IP multimedia call and/or said set of service applications for answering said incoming call using an HyperText Transfer  
20 Protocol session.

An alternative feature of the present invention is described in claim 7.

The call presentation information forwarding means of the Primary Application Server is able to forward the call presentation  
25 information of said incoming IP multimedia call and/or said set of service applications for answering said incoming call via an Wireless Application Protocol session.

An alternative feature of the present invention is described in claim 8.

The call presentation information forwarding means of the Primary Application Server is able to forward said call presentation  
5 information of said incoming IP multimedia call and/or said set of service applications for answering the incoming call via the Call session control network element (CSCF).

A further characteristic feature of the present invention is described in claim 10.

10 The application presentation means of the Called Party Terminal is implemented using a web-browser.

It is to be noticed that the term 'comprising', used in the claims, should not be interpreted as being restricted to the means listed thereafter. Thus, the scope of the expression 'a device comprising means  
15 A and B' should not be limited to devices consisting only of components A and B. It means that with respect to the present invention, the only relevant components of the device are A and B.

Similarly, it is to be noticed that the term 'coupled', also used in the claims, should not be interpreted as being restricted to direct  
20 connections only. Thus, the scope of the expression 'a device A coupled to a device B' should not be limited to devices or systems wherein an output of device A is directly connected to an input of device B. It means that there exists a path between an output of A and an input of B which may be a path including other devices or means.

25 The above and other objects and features of the invention will become more apparent and the invention itself will be best understood by referring to the following description of an embodiment taken in conjunction with the accompanying drawings wherein:

Fig. 1 represents a part of an Internet Protocol Multimedia Network IMMN wherein the application server selection method is applied;

Fig. 2 represents the functional structure of a call session control network element CSCF, a primary application server AS<sub>PRIM</sub> and a called party terminal CDPT as presented in FIG.1.

In the following paragraphs, referring to the drawings, an implementation of the method and the related devices according to the present invention will be described. In the first paragraph of this description the main elements of this network as presented in FIG. 1 are described. In the second paragraph, the connections between the before mentioned network elements and described means are defined. Subsequently all relevant functional means of the mentioned network elements are described followed by a description of all interconnections. In the succeeding paragraph the actual execution of the method for session establishment is described.

The part of the Internet Protocol Multimedia Network IMMN presented in figure 1 comprises two Call session control network elements CCin, CSCF which deal with establishment of calls between a calling party CGPT and two or more called parties CDPT, CDPT1. The first Call session control network elements CCin is responsible for serving the calling party CGPT and the second Call session control network elements CSCF is responsible for serving the called party CDPT. It is assumed that, but is not mandatory that the second Call session control network elements CSCF is responsible for a second called party terminal CDPT1. Furthermore there is a primary application server AS<sub>PRIM</sub> that is able to provide a called party CDPT, CDPT1 with the option to select an application server from a set of application servers AS1..ASn for

answering an incoming call and further a called party terminal CDPT that is adapted to select an application from a set of application services for answering an incoming call. Further there is a calling party terminal CGPT. All user-terminals CGPT and CDPT, CDPT1 are chosen to  
5 be a personal computer with a belonging screen and keyboard and a mouse further comprising a microphone and speaker for the provisioning of telephone functionality. Although in this embodiment only two called party terminals CDPT, CDPT1 are presented, it is not excluded that there are more terminals. Moreover there is a plurality of Application servers  
10 AS1..ASn that provide the called party with services such as additional methods of payment (possibly assisted with additional interfacing possibilities such as e.g. a Web interface), additional means of controlling the call e.g. for adding, modifying, or deleting resources involved in the call, such as media resources, or monitoring or recording  
15 equipment, also possibly assisted with additional interfacing possibilities such as a Web interface, etc. It is to be noted that the completion of the call can be conditioned to the availability of these resources, depending on user preferences and/or user subscriptions.

Although there can be more than three user terminals CGPT, CDPT and CDPT1 and more than two Call session control network elements CCin and CSCF in such an internet protocol multimedia network, only these elements are described in this embodiment in order to keep simplicity.

The calling party terminal CGPT is coupled to the first Call session control network element CCin over an Internet protocol link,  
25 further referred to as an IP-link. Further this first Call session control network element CCin is coupled to the second Call session control network element CSCF over an IP-link and the called party terminal CDPT

is also coupled to the Call session control network element CSCF over an IP-link. Moreover, the primary application server AS<sub>PRIM</sub> and the further application servers AS<sub>1</sub>..AS<sub>n</sub> each is coupled to the second Call session control network elements CSCF using an IP-link. The network elements  
5 communicate using Session Initiation Protocol Messages. Alternatively it is possible to use the protocols from the H.323 protocol family as appropriate.

The Call session control network element CSCF comprises a call intercepting means CIM that is able to intercept an incoming IP  
10 multimedia call and a Primary Application Server invocation means PASIM that is able to invoke, upon intercepting an incoming IP multimedia call, a primary Application Server AS<sub>PRIM</sub> and forward call data corresponding to said incoming IP multimedia call to said Primary Application Server AS<sub>PRIM</sub>. The Call session control network element CSCF  
15 further comprises a Selection receiving means SRM that is adapted to receive from said Primary Application Server AS<sub>PRIM</sub> a selection of at least one service application forwarded by the called party terminal CDPT and a Secondary Application server invocation means SASIM that is able to activate based on the at least one selected service application at  
20 least one secondary Application Server AS<sub>1</sub>..AS<sub>n</sub> corresponding to the at least one selected service application.

If there is more than one Application Service selected each of the selected application servers are subsequently activated.

The Primary Application Server AS<sub>PRIM</sub> comprises an activation  
25 message reception means ARM that is adapted to receive call data corresponding to the incoming IP multimedia call forwarded by said Call Session Control network element CSCF, a call analysis means CAM that is able to analyse the incoming IP multimedia call and based on this

analysis determine a set of service applications for answering the incoming call and a call presentation information forwarding means CPM that is adapted to forward, upon analysis of the incoming IP multimedia call, the call presentation information of the incoming IP multimedia call to the called party terminal CDPT together with a presentation of a set of service applications for answering the incoming call. The set of service applications wherefrom the user may select service applications is determined in the analysis of the incoming IP Multimedia call.

Furthermore the Primary Application Server AS<sub>PRIM</sub> is built up of a user selection reception means USRM that is able to receive from the called party terminal CDPT a selection of at least one service application from the set of service applications forwarded by the called party terminal CDPT and an application selection forwarding means ASFM that is able to forward this selection of at least one service application from the set of service applications forwarded by the called party terminal CDPT towards the call session control Network element CSCF.

The final relevant network element is the Called Party Terminal CDPT for selecting an Application Server in an Internet Protocol multimedia network IMMN upon reception of an Internet Protocol Multimedia Call by the Call Session Control network element CSCF. This Called Party Terminal CDPT is built up of an Application Presentation Reception means APRM that is able to receive call presentation information of the incoming IP multimedia call together with a presentation of a set of service applications for answering the incoming call from the Primary Application Server AS<sub>PRIM</sub> and an application presentation means APM that is able to make a call presentation of the incoming IP multimedia call to the called party terminal CDPT together



with a presentation of a set of service applications for answering the incoming call. The Called Party Terminal CDPT further comprises an application selection means ASM that is adapted to select at least one service application of the presented set of service applications  
5 forwarded by the called party terminal CDPT and a user application selection forwarding means UASFM that is adapted to forward a selection of at least one service application of the set of service applications forwarded by the called party terminal CDPT towards the call session control Network element CSCF.

10 The call intercepting means CIM of the call session control Network element CSCF has an input-terminal that is at the same time an input-terminal  $I_0$  of the call session control Network element CSCF. The call intercepting means CIM further possess an output that is coupled to an input- of the Primary Application Server invocation means PASIM  
15 which in its turn possess an output-terminal that is at the same time an output-terminal terminal  $O_1$  of the call session control Network element CSCF.

The Selection receiving means SRM has an input-terminal that is at the same time an input-terminal  $I_1$  of the call session control Network  
20 element CSCF and an output that is coupled to an input of the Secondary Application server invocation means SASIM that further possess an output-terminal that is at the same time an output-terminal  $O_2$  of the call session control Network element CSCF.

The activation message reception means ARM of the Primary  
25 Application Server  $AS_{PRIM}$  has an input-terminal that is at the same time an input-terminal  $I_2$  of the Primary Application Server  $AS_{PRIM}$ . Furthermore, the activation message reception means ARM possess an output that is coupled to an input of the call analysis means CAM that in its turn is

coupled with an output to an input of the call presentation information forwarding means CPM. The call presentation information forwarding means CPM has an output-terminal that is at the same time an output-terminal O<sub>3</sub> of the Primary Application Server AS<sub>PRIM</sub>. The user selection reception means USRM has an input-terminal that is at the same time an input-terminal I<sub>3</sub> of the Primary Application Server AS<sub>PRIM</sub>. This user selection reception means USRM further is coupled with an output to an input of the application selection forwarding means ASFM. Moreover the application selection forwarding means ASFM has an output-terminal that is at the same time an output-terminal O<sub>4</sub> of the Primary Application Server AS<sub>PRIM</sub>.

The Application Presentation Reception means APRM of the called party terminal CDPT possess an input-terminal that is at the same time an input-terminal I<sub>4</sub> of the called party terminal CDPT and an output that is coupled to an input- of the application presentation means APM that in its turn is coupled with an output to an input of the application selection means ASM. Furthermore the application selection means ASM is coupled with an output to an input of the user application selection forwarding means UASFM. The user application selection forwarding means UASFM possess an output-terminal that is at the same time an output-terminal O<sub>5</sub> of the called party terminal CDPT.

The Primary Application Server AS<sub>PRIM</sub> is coupled with its output-terminal O<sub>3</sub> to input-terminal I<sub>4</sub> of the called party Terminal CDPT. Additionally, the Primary Application Server AS<sub>PRIM</sub> is coupled with its input-terminal I<sub>3</sub> to output-terminal O<sub>5</sub> of the called party Terminal CDPT.

In order to explain the operation of the present invention it is assumed that the calling party uses its terminal CGPT for setting up a call to the called user party terminal CDPT. It is supposed that the calling user

party therefore makes use of a well known phone application (or any special application he might have for making calls such as voice or multimedia calls) at his terminal. The signalling in the call set-up is performed using the session initiation protocol by sending a SIP INVITE  
5 message towards the second call session control network element CSCF via the first call session control network element CC<sub>IN</sub>. The handling of the SIP message at the first call session control network element CC<sub>IN</sub> is not relevant for explaining the present invention and is as a consequence not described. The SIP INVITE message is forwarded to the  
10 call session control network element CSCF.

The call intercepting means CIM of the Call Session Control network element CSCF intercepts the incoming IP multimedia call i.e. the SIP INVITE message. The message is forwarded towards the Primary Application Server invocation means PASIM that invokes, upon  
15 intercepting the incoming IP multimedia call, a primary Application Server AS<sub>PRIM</sub> by forwarding call data corresponding to the incoming IP multimedia call to this Primary Application Server AS<sub>PRIM</sub>, with possibly additional information that is part of the called party user profile that is contained in the CSCF.

20 The activation message reception means ARM of the Primary Application Server AS<sub>PRIM</sub> then receives the call data corresponding to said incoming IP multimedia call, i.e. the SIP INVITE message forwarded by the Call Session Control network element CSCF. At forwarding of this call data, the call analysis means CAM analyses this incoming IP  
25 multimedia call and based on this analysis determines a set of service applications for answering the incoming call; the elements of information that are analysed by the CAM are parts of the call data, i.e. parts of the SIP INVITE message, which are called in the 3GPP standard Service Point

Triggers (SPTs), and parts or all of the data that was possibly added by the CSCF.

It is assumed that after analysis it appears that the called party has the option to answer the call for instance as an ordinary phone call,  
5 to additionally record this call, to establish a three party call or to establish a connection with a certain Quality of Service It is to be noted that any combination of features is possible.

It is further assumed that the called party at reception of the incoming call wants to record the call as evidence of content of the  
10 spoken words could be useful for some reason and additionally it is necessary to involve a third party in the call for instance for provisioning expert knowledge.

Subsequently, the call presentation information forwarding means CPM forwards, upon analysis of the incoming IP multimedia call,  
15 call presentation information of the incoming IP multimedia call to the called party terminal CDPT together with a presentation of a set of service applications for answering the incoming call. This presentation may be done using a dedicated HTTP session and an internet browser running at the called party terminal CDPT for presenting the set of service  
20 applications and facilitating to select service application from this set of applications. This set of service applications is determined in the analysis. Alternatively, the forwarding of the set of service applications may also be performed towards the call session control network element CSCF that in its turn forwards the data towards the called party terminal CDPT.  
25 The Application Presentation Reception means APRM of the called party Terminal CDPT receives the call presentation information of the incoming IP multimedia call together with the presentation of the set of service applications for answering the incoming call from the Primary

Application Server AS<sub>PRIM</sub>. Subsequently, the application presentation means APM deals with the call presentation, of said incoming IP multimedia call to the called party terminal CDPT together with a set of service applications for answering the incoming call. The presentation  
5 means may be an internet browser that displays the information corresponding to the incoming call on the screen of the user terminal. Here it is assumed that the called party at reception of the incoming call wants to record the call as evidence of content of the spoken words which could be useful for some reason and additionally it is necessary to  
10 involve a third party in the call for provisioning expert knowledge. The recording of the conversation is to be performed by activating a corresponding service application to be executed by a secondary application server, assume application server AS1. The establishment of the three party call, that is making a selection of the third party to be  
15 involved in the call from a list and subsequently adding this selected party to the call parties is to be performed by activating a corresponding service application to be executed by another secondary application server, assume application server AS2.

The selection of service applications as presented on the  
20 screen of the called party terminal CDPT is dealt with by the application selection means ASM. This application selection means ASM for instance comprises a mouse for selecting the service applications by clicking icons representing the service applications on the screen of the called user party terminal CDPT. The user then selects application service AS1  
25 and subsequently application service AS2 by clicking the corresponding icons on the screen or by dragging and dropping these icons in a special area or window called activation window. Then the user application selection forwarding means UASFM will forward the selection

of the service applications AS1, AS2 from the set of service applications AS1.. ASn forwarded by the called party terminal CDPT towards the user selection reception means USRM of the Primary Application Server AS<sub>PRIM</sub>. The user selection reception means USRM of the Primary Application  
5 Server AS<sub>PRIM</sub>, receives the selection of the service applications AS1, AS2 forwarded by said called party terminal CDPT and subsequently forwards this selection towards the application selection forwarding means ASFM that in its turn forwards this selection towards the call session control Network element CSCF. The Selection receiving means SRM of the call  
10 session control network element CSCF then receives from said Primary Application Server AS<sub>PRIM</sub> this selection of the service applications AS1, AS2. Subsequently, the Secondary Application server invocation means SASIM activates based on the selection of service applications SA1, SA2 subsequently the secondary Application Servers AS1, AS2 that  
15 correspond to the selected service applications AS1, AS2.

The activated secondary Application Server(s) perform their function, i.e. initialise the recording tool and subsequently provide the called user party terminal with an option to select the third party that should be involved in the call.

20 A final remark is that embodiments of the present invention are described above in terms of functional blocks. From the functional description of these blocks, given above, it will be apparent for a person skilled in the art of designing electronic devices how embodiments of these blocks can be manufactured with well-known electronic  
25 components. A detailed architecture of the contents of the functional blocks hence is not given.

While the principles of the invention have been described above in connection with specific apparatus, it is to be clearly

understood that this description is made only by way of example and not as a limitation on the scope of the invention, as defined in the appended claims.